

## Product Overview

### Fast Ethernet managed Multiport Converter 24 x 100Base-TX/FX



## Description

With the new generation of multiport media converter it is possible to realise the media conversion of up to 24 ports in 1 height unit (1 HU). This port density can be reached also with the standard optical connectors such as ST- and SC-duplex.

Beside this high port density the actual 24 port converter has several additional features such as SNMP/web-based management, optional redundant power supply and auto-crossing integrated. The MICROSENS converter are designed for the installation into 19" racks. With this compact design it is possible to reach very high port densities in the central distribution racks.

The connection to the central switch is done, depending on the version, by Telco or RJ-45 cable. The Telco cables are having an RJ-21 connector with a capacity of 12 twisted-pair connections and offer flexibility and simple installation.

## Properties

- Compact design, lowest costs per port
- Cost optimised, repeaterless copper/fiber conversion
- Simple handling/installation
- Support of half- and full-duplex connections
- Integrated management, stackable
- Optional redundant power supply

## Order Information

Description	Article Number
<b>RJ-45 Anschlüsse</b>	
24 Port Fast Ethernet Media Converter Multimode 1310nm ST, 19"1U, RJ-45, manageable	<b>MS416900M</b>
24 Port Fast Ethernet Media Converter Multimode 1310nm SC, 19"1U, RJ-45, manageable	<b>MS416901M</b>
24 Port Fast Ethernet Media Converter Single mode 1310nm ST, 15km , 19"1U, RJ-45, manageable	<b>MS416905M</b>
24 Port Fast Ethernet Media Converter Single Mode 1310nm SC, 15km, 19"1U, RJ-45, manageable	<b>MS416906M</b>
<b>TELCO Anschlüsse</b>	
24 Port Fast Ethernet Media Converter Multimode 1310nm ST, 19"1U, manageable	<b>MS416920M</b>
24 Port Fast Ethernet Media Converter, 1310 nm Multimode SC, 19"1U, TELCO, manageable	<b>MS416921M</b>
24 Port Fast Ethernet Media Converter, Single Mode 1310nm ST, 19"1U, TELCO, manageable	<b>MS416925M</b>
24 Port Fast Ethernet Media Converter Multimode 1310nm MT-RJ, 19"1U, TELCO, manageable	<b>MS416929M</b>

## Accessories

<b>Description</b>	<b>Article Number</b>
RPSU unit for the supply of up to 6 converter systems (24 Port FX/TX), RPSU interface for MS41692xM	<b>MS416031</b>
RPSU cable, x: length in m	<b>MS190450-x</b>
nmp Professional - MICROSENS Network Management Platform - java software and one year update license	<b>MS200160-1</b>
Power cord EU/C13 with locking system, 3x1mm <sup>2</sup> (US:AWG18) black 2m	<b>MS190004VS</b>
Power cord UK/C13 with locking system, 3x1mm <sup>2</sup> (US:AWG18) black 2m	<b>MS190005VS</b>
Power cord US/C13 with locking system, 3x1mm <sup>2</sup> (AWG18) black 2m	<b>MS190006VS</b>

This document in whole or in part may not be duplicated, reproduced, stored or retransmitted without prior written permission of MICROSENS GmbH & Co. KG. All information in this document is provided 'as is' and subject to change without notice. MICROSENS GmbH & Co. KG disclaims any liability for the correctness, completeness or quality of the information provided, fitness for a particular purpose or consecutive damage. MICROSENS is a trademark of MICROSENS GmbH & Co. KG. Any product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

© 2015.11.23 MICROSENS GmbH & Co. KG - 59067 Hamm/Germany - Tel. +49 2381 9452-0 - [www.microsens.com](http://www.microsens.com)